

Grabo Aura

Technical parameter	Standard	Unit	Result
DESCRIPTION			
Construction			Light-Commercial heterogeneous
Total thickness	EN ISO 24346	mm	2.0
Width of roll	EN ISO 24341	m	2 / 4
Length of roll	EN ISO 24341	lm	25
Total weight	EN 430	kg/m ²	1.8
CLASSIFICATION			
European classification	ISO 10874	class	23/32/41
Residual indentation	EN ISO 24343-1	max. mm	0.2
Dimensional stability	EN ISO 23999	max. %	0.2
PERFORMANCE			
Abrasion group	MSZ EN 660-1	class	T
Fire resistance	EN 13501-1	class	Bfl-s1
	DIN 51130		R9
Slip resistance	EN 13893		DS
Electrical resistance	EN 1815	kV	< 2
Chemical resistance	EN ISO 26987		✓
Bacterial resistance	EN ISO 846:1999		✓
Light fastness	EN 20105 B02	grade	min.6
Castor chair resistance	ISO 4918		✓
Environmental attributes			Solvent and heavy metal free 100% recyclable
Content of PCP	EN 12673		No
Formaldehyde emission	ENV 717-1		E1 (No Emission)
Seaming method			heat or cold weld
Warranty		year	7
CE MARKING	EN 14041		✓

GRABOPLAST Floor Covering Manufacturers Ltd.
H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100
mail@graboplast.hu www.graboplast.hu