

Thickness
5.0 mm
Wear layer
0.3 mm


43


iGuard


GLASS FIBRE
REINFORCEMENT

PUx3*

100%
WATER
RESISTANT



PHTHALATE
FREE

GRABOPLAST
Padlógyártó zrt.
9023 Győr, Fehérvári u. 16/b.

GRABO DOMINO SPC

SPECIFICATION

CONSTRUCTION	SPC Luxury floor with click	
PLANK SIZE	EN ISO 24341	177,8×1219,2 mm
	EN ISO 24341	7×48 inch
THICKNESS	EN ISO 24346	5.0 mm
WEAR LAYER	EN ISO 24340	0.3 mm
TOTAL WEIGHT	EN ISO 23997	7.9 kg/m ²

CLASSIFICATION

BINDER CONTENT	EN ISO 10582	Type I.
EUROPEAN CLASSIFICATION	EN ISO 10582	class: 23/33/43
RESIDUAL INDENTATION <small>REQUIREMENT</small>	EN ISO 24343	max. 0.1 mm
RESIDUAL INDENTATION <small>MEASURED VALUE</small>	EN ISO 24343	max. 0.03 mm
DIMENSIONAL STABILITY	EN ISO 23999	max. 0.15 %
CURLING	EN ISO 23999	max. 2 mm

PERFORMANCE

ABRASION GROUP	MSZ EN 660-1	class: T
FIRE RESISTANCE	EN 13501-1	class: Bfl-s1
SLIP RESISTANCE	EN 13893	DS
	DIN 51130	R10
LIGHT FASTNESS	EN ISO 105-B0	grade 6
CHEMICAL RESISTANCE	EN ISO 26987	✓
HYGENIE		✓
ENVIRONMENTAL ATTRIBUTES	solvent and phthalate free	
SURFACE TREATMENT	iGuard PUR Surface	
CONTENT OF PCP	EN 12673	does not contain
FORMALDEHIDE EMISSION	ENV 717-1	E1 (no emission)

GRABOPLAST

FLOOR COVERING MANUFACTURERS LTD.

H-9023 Győr, Fehérvári út. 16/b. Phone: (+36) 96 506-100

www.graboplast.com



2019 | 01



www.facebook.com/graboplast

GRABO
DOMINO SPC

* Triple PU - Exclusively for Russia, Kazakhstan, Armenia